AUTHOR INDEX

Allgood, A., p. 31
Bar-Yaacov, R., p. 181
Barda, H.J., p. 245
Beninate, J.V., p. 53
Brown, R.J., p. 102
Chance, L.H., p. 188
Das, M., p. 23
Drake, G.L., Jr., p 53
Eldridge, W.J., p. 245
Fearing, R.B., p. 39
Franklin, N.E., p. 84
Gibilisco, R.D., p. 232
Gourghiotis, D.J., p. 94
Green, J., p. 194, 232
Haines, P.J., p. 23
Hammons, M.A., p. 31
Hobart, S.R., p. 135
Hughes, K.A., p. 155
Jaffe, F., p. 39
Jensen, J.C., p. 209
Keating, J.Z., p. 215
Kintz, D.P., p. 13
Kishore, K., p. 115, 172
Kourtides, D.A., p. 181
Lee, F.H., p. 232
Lee, F.T., p. 194
Lever, T.J., p. 23
Madacsi, J.P., p. 70
Mikroyannidis, J.A., p. 3, 94
Minke, R., p. 181
Mohandas, K., p. 115, 172
Neumeyer, J.P., p. 70
Nicholson, P., p. 194
Nir, Z., p. 181
Parker, J.A., p. 181
Reeves, W.A., p. 31
Rose, R.S., p. 155, 209
Rowland, S.P., p. 135
Shen, K.K., p. 161
Skinner, G.A., p. 23
Sprague, R.W., p. 161
Termine, E.J., p. 221
Timpa, J.D., p. 188
Touval, I., p. 181
Trask, B.J., p. 53
Tsolis, A.K., p. 3, 94
Uhlman, J.G., p. 221
Weil, E.D., p. 39
Whitaker, W.A., p. 13

SUBJECT INDEX

Additives, p. 3, 94
Antimony oxide, p. 13, 31
Boric acid, p. 70
Brominated pentaerythritol, p. 221
Brominated polyols, p. 245
Bromine, p. 181
Bromotriazines, p. 188
Burning mode, p. 135
Burning rate, cotton, p. 135
Burning rates, depending on FR concentration, p. 172
Cellulose, p. 3, 84, 94
Char layer formation, PVC, p. 102
Char residue, p. 135
Combustion atmosphere, p. 135
Cotton, p. 84, 188
Cotton batting, p. 70
Cotton blends, FR, p. 53
Cotton/modacrylic blends, p. 31
Crease resistance, p. 3, 94
1,2-Dihydroxy-1,2-bis (dimethoxyphosphinyl)ethane, p. 94
Electrical laminate, p. 161
Encapsulation, p. 161
Epoxy, p. 161
Extenders, p. 70
Finishing process, p. 3, 94
Fire Resistance, p. 3, 31
Flame retardant, p. 84, 155, 161, 181, 188, 209, 221, 245
Flame retardant, reactive, p. 194, 232
Flame temperature, p. 135
Flame temperature, monitor, p. 135
Flammability rates, FR cotton blends, p. 53
Flexible polyurethane foams, p. 215
Formaldehyde, p. 188
Halogenated polyester thermosets, p. 23

AUTHOR INDEX

Allgood, A., p. 31
Bar-Yaacov, R., p. 181
Barda, H.J., p. 245
Beninate, J.V., p. 53
Brown, R.J., p. 102
Chance, L.H., p. 188
Das, M., p. 23
Drake, G.L., Jr., p 53
Eldridge, W.J., p. 245
Fearing, R.B., p. 39
Franklin, N.E., p. 84
Gibilisco, R.D., p. 232
Gourghiotis, D.J., p. 94
Green, J., p. 194, 232
Haines, P.J., p. 23
Hammons, M.A., p. 31
Hobart, S.R., p. 135
Hughes, K.A., p. 155
Jaffe, F., p. 39
Jensen, J.C., p. 209
Keating, J.Z., p. 215
Kintz, D.P., p. 13
Kishore, K., p. 115, 172
Kourtides, D.A., p. 181
Lee, F.H., p. 232
Lee, F.T., p. 194
Lever, T.J., p. 23
Madacsi, J.P., p. 70
Mikroyannidis, J.A., p. 3, 94
Minke, R., p. 181
Mohandas, K., p. 115, 172
Neumeyer, J.P., p. 70
Nicholson, P., p. 194
Nir, Z., p. 181
Parker, J.A., p. 181
Reeves, W.A., p. 31
Rose, R.S., p. 155, 209
Rowland, S.P., p. 135
Shen, K.K., p. 161
Skinner, G.A., p. 23
Sprague, R.W., p. 161
Termine, E.J., p. 221
Timpa, J.D., p. 188
Touval, I., p. 181
Trask, B.J., p. 53
Tsolis, A.K., p. 3, 94
Uhlman, J.G., p. 221
Weil, E.D., p. 39
Whitaker, W.A., p. 13

SUBJECT INDEX

Additives, p. 3, 94
Antimony oxide, p. 13, 31
Boric acid, p. 70
Brominated pentaerythritol, p. 221
Brominated polyols, p. 245
Bromine, p. 181
Bromotriazines, p. 188
Burning mode, p. 135
Burning rate, cotton, p. 135
Burning rates, depending on FR concentration, p. 172
Cellulose, p. 3, 84, 94
Char layer formation, PVC, p. 102
Char residue, p. 135
Combustion atmosphere, p. 135
Cotton, p. 84, 188
Cotton batting, p. 70
Cotton blends, FR, p. 53
Cotton/modacrylic blends, p. 31
Crease resistance, p. 3, 94
1,2-Dihydroxy-1,2-bis (dimethoxyphosphinyl)ethane, p. 94
Electrical laminate, p. 161
Encapsulation, p. 161
Epoxy, p. 161
Extenders, p. 70
Finishing process, p. 3, 94
Fire Resistance, p. 3, 31
Flame retardant, p. 84, 155, 161, 181, 188, 209, 221, 245
Flame retardant, reactive, p. 194, 232
Flame temperature, p. 135
Flame temperature, monitor, p. 135
Flammability rates, FR cotton blends, p. 53
Flexible polyurethane foams, p. 215
Formaldehyde, p. 188
Halogenated polyester thermosets, p. 23

Hydrated alumina, p. 215
2-Hydroxy-2-(dialkoxyphosphinyl) ethanals, p. 94
Kinetics, p. 84
Laminates, FR, p. 13
Low smoke, polyurethane foam, p. 209, 215
Mechanisms, p. 84
N-methylol resins, p. 31
Molybdenum trioxide, p. 23
Oligomers, p. 39
Oxygen index, p. 31
Paper, flame retardants for, p. 39
Phosphates, p. 39
Phosphonates, p. 39
Phosphorus flame retardant, p. 194, 232
Polybutylene, p. 181
Polycondensation, p. 39
Polymer flammability, p. 115
Polymer ignition, p. 115
Polystyrene, p. 115
Polyurethanes, flame retardants for, p. 39
Polyurethane foam, p. 155, 209
Pyrolysis, p. 84
Rigid PVC, FR, p. 102
Rigid polyurethane, flame retardant for, p. 194, 209, 221, 232, 245
Scorch, p. 155
Smoke suppressant, p. 23, 161
Smolder, p. 155
Smoldering combustion, p. 70
Smolder rate, p. 70
Substitutes, p. 70
Surface/edge ignition, cotton, p. 53
Thermogravimetric analysis, p. 84
THPOH-NH_3, p. 135
Tetrabromophthalate diol, p. 209
Textile, backcoating with flame retardants, p. 39
Vinyl phosphonate-N-methylalacrylamide, p. 135